

Mounty® 90 L

Portable Chain Feeds



Lightweight, portable chain feed, fully pneumatic, ideal for all handy drilling operations; can be used with down-the-hole hammer as well as with drill hammer. Uncoiled for easy mounting on any type of scaffolding; suitable for wall work.

- Chain feed, fixing plate for scaffolding tubes, combination guide retraction force 7 kN / 6 bar.
- Rotary head 900 Nm / 6 bar
- Control battery with oiler and hoses
- Telescopic support 2.2 – 3.6 m

Mounty 90L package

- Mounty 90L, feed length 1.30, 1.80 or 2.4 m
- Rotary head NLL
- Control panel SLL
- Rack back stay



Technical specifications

Mounty® 90 L

Specifications



Operating weight excavator t

Weight ¹ kg > 45

Oil requirement l/min / bar

Feed / Retrait force kN 9

Torque max. daNm 90

Feed mm 1'300 / 1'800 / 2'300

Dimensions (LxBxH) mm 2'160 / 580 / 650

Chain feed profil BL 90

Fixing plate for scaffolding tube inclusive

Rotary plate for scaffolding tube inclusive

Clamp mm

Top hammer daNm 35

Rotary drive daNm 90

Double head daNm

Deliverable with

Hydraulic control panel inclusive

Radio or cable control optional

Digital display radio control

Anti jamming system

Adjustable percussion mechanism

Injection pump control optional

Threaded gear

Swivel 90° (mechanical) optional

Breaking device optional

Drilling guide inclusive

Rack back stay inclusive

Requirements hydraulic power units

Weight kg

Engine power kW


Fuel

Hose length m

Drilling methods Application ideal Application conditionally possible

Blast hole / Rock drilling	ø mm	33	45	57	76	89
KSB® Anchor drilling	ø anchor	R32	R38	R51	T76	T114
Rotate- / Downhole Drilling	ø mm	70	90	140	178	250
Casing drilling	ø mm	114	139	168	178	219
Core drilling	inch	100	131	146	200	254
Injection connector	mm	3/8"				

1. Without safety device according to standard EN16228



Rotary percussion drilling



Rotating uniped



Pneumatic drive

System drawing

